


DG M TNS 275 (952 400)


- Prewired complete unit consisting of a base part and plug-in protection modules
- High discharge capacity due to heavy-duty zinc oxide varistors/spark gaps
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG M TNS 275



Dimension drawing DG M TNS 275

Modular surge arrester for use in TN-S systems

| Type | DG M TNS 275 |
|---|---|
| Part No. | 952 400 |
| SPD according to EN 61643-11 | Type 2 |
| SPD according to IEC 61643-1/-11 | Class II |
| Nominal a.c. voltage (U_N) | 230/400 V |
| Max. continuous operating a.c. voltage (U_C) | 275 V |
| Nominal discharge current (8/20 μ s) (I_n) | 20 kA |
| Max. discharge current (8/20 μ s) (I_{max}) | 40 kA |
| Voltage protection level (U_P) | ≤ 1.25 kV |
| Voltage protection level at 5 kA (U_P) | ≤ 1 kV |
| Response time (t_A) | ≤ 25 ns |
| Max. mains-side overcurrent protection | 125 A gL/gG |
| Short-circuit withstand capability for max. mains-side overcurrent protection | 50 kA _{rms} |
| Temporary overvoltage (TOV) (U_T) | 335 V / 5 sec. |
| TOV characteristic | withstand |
| Operating temperature range (T_U) | -40°C...+80°C |
| Operating state/fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (min.) | 1.5 mm ² solid/flexible |
| Cross-sectional area (max.) | 35 mm ² stranded/25 mm ² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 4 module(s), DIN 43880 |
| Approvals | KEMA, VDE, UL, VdS |
| Weight | 443 g |
| Customs tariff number | 85363030 |
| GTIN | 4013364108455 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.