

Product Data Sheet: DEHNsecure M




NEW DSE M 2P 60 (971 221)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Spark gap technology particularly suited for use in d.c. circuits
- Directly coordinated with DEHNGuard surge protective device without additional cable length



Figure without obligation



Basic circuit diagram DSE M 2P 60



Dimension drawing DSE M 2P 60

Coordinated modular two-pole lightning current arrester for d.c. applications from 12 to 60 volts ("1+1" circuits); FM version with floating remote signalling contact

Type	DSE M 2P 60
Part No.	971 221
SPD classification according to EN 61643-11	Type 1
SPD classification according to IEC 61643-1/11	Class I
Max. continuous operating d.c. voltage (U_c)	60 V
Lightning impulse current (10/350 µs) (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$)	25 / 50 kA
Specific energy (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$) (W/R)	156.25 kJ/ohms / 625.00 kJ/ohms
Nominal discharge current (8/20 µs) (I_n)	25 kA
Voltage protection level (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$) (U_P)	$\leq 1.5 \text{ kV} / \leq 1.5 \text{ kV}$
Response time (t_A)	$\leq 100 \text{ ns}$
Short-circuit withstand capability for max. mains-side overcurrent protection d.c.	2000 A
Max. mains-side overcurrent protection	250 A gL/gG
Max. backup fuse (DC+/DC- → DC+'/DC-')	125 A gL/gG
Operating temperature range (parallel connection) (T_{UP})	-40°C...+80°C
Operating temperature range (series connection) (T_{US})	-40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	10 mm ² solid/flexible
Cross-sectional area (DC+/DC-, DC-/DC+, $\frac{1}{2}$) (max.)	50 mm ² stranded/35 mm ² flexible
Cross-sectional area (DC+'/DC-, DC-'/DC+') (max.)	35 mm ² stranded/25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Weight	608 g
Customs tariff number	85363030
GTIN	4013364138612
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.