


NEW DSE M 2P 60 FM (971 226)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Spark gap technology particularly suited for use in d.c. circuits
- Directly coordinated with DEHNGuard surge protective device without additional cable length



Figure without obligation



Basic circuit diagram DSE M 2P 60 FM



Dimension drawing DSE M 2P 60 FM

Coordinated modular two-pole lightning current arrester for d.c. applications from 12 to 60 volts ("1+1" circuits); FM version with floating remote signalling contact

| Type | DSE M 2P 60 FM |
|---|---|
| Part No. | 971 226 |
| SPD classification according to EN 61643-11 | Type 1 |
| SPD classification according to IEC 61643-1/11 | Class I |
| Max. continuous operating d.c. voltage (U_c) | 60 V |
| Lightning impulse current (10/350 µs) (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$) | 25 / 50 kA |
| Specific energy (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$) (W/R) | 156.25 kJ/ohms / 625.00 kJ/ohms |
| Nominal discharge current (8/20 µs) (I_n) | 25 kA |
| Voltage protection level (DC+/DC- → DC-/DC+) (DC-/DC+ → $\frac{1}{2}$) (U_P) | $\leq 1.5 \text{ kV} / \leq 1.5 \text{ kV}$ |
| Response time (t_A) | $\leq 100 \text{ ns}$ |
| Short-circuit withstand capability for max. mains-side overcurrent protection d.c. | 2000 A |
| Max. mains-side overcurrent protection | 250 A gL/gG |
| Max. backup fuse (DC+/DC- → DC+/DC-') | 125 A gL/gG |
| Operating temperature range (parallel connection) (T_{UP}) | -40°C...+80°C |
| Operating temperature range (series connection) (T_{US}) | -40°C...+60°C |
| Operating state/fault indication | green / red |
| Number of ports | 1 |
| Cross-sectional area (min.) | 10 mm ² solid/flexible |
| Cross-sectional area (DC+/DC-, DC-/DC+, $\frac{1}{2}$) (max.) | 50 mm ² stranded/35 mm ² flexible |
| Cross-sectional area (DC+/'/DC-', DC-/'/DC+') (max.) | 35 mm ² stranded/25 mm ² flexible |
| For mounting on | 35 mm DIN rails acc. to EN 60715 |
| Enclosure material | thermoplastic, red, UL 94 V-0 |
| Place of installation | indoor installation |
| Degree of protection | IP 20 |
| Capacity | 4 module(s), DIN 43880 |
| Type of remote signalling contact | changeover contact |
| a.c. switching capacity | 250 V/0.5 A |
| d.c. switching capacity | 250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A |
| Cross-sectional area for remote signalling terminals | max. 1.5 mm ² solid/flexible |
| Weight | 611 g |
| Customs tariff number | 85363030 |
| GTIN | 4013364138629 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.