

# Product Data Sheet: DEHNguard® modular




## DG M TT 150 FM (952 328)


- Prewired complete unit consisting of a base part and plug-in protection modules
- High discharge capacity due to heavy-duty zinc oxide varistors/spark gaps
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG M TT 150 FM



Dimension drawing DG M TT 150 FM

Modular surge arrester for use in TT and TN-S systems ("3+1" circuit); with floating remote signalling contact

| Type  | DG M TT 150 FM  |
|---|---|
| Part No.  | 952 328   |
| SPD according to EN 61643-11  | Type 2  |
| SPD according to IEC 61643-1/1-11   | Class II  |
| Nominal a.c. voltage ( $U_N$ )  | 120/240 V   |
| Max. continuous operating a.c. voltage [L-N] ( $U_C$ )                        | 150 V   |
| Max. continuous operating a.c. voltage [N-PE] ( $U_C$ )                       | 255 V   |
| Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )                            | 15 kA   |
| Max. discharge current (8/20 $\mu$ s) ( $I_{max}$ )                           | 40 kA   |
| Lightning impulse current (10/350 $\mu$ s) [N-PE] ( $I_{imp}$ )               | 12 kA   |
| Voltage protection level [L-N] ( $U_P$ )                                      | $\leq 0.7$ kV   |
| Voltage protection level [L-N] at 5 kA ( $U_P$ )                              | $\leq 0.55$ kV  |
| Voltage protection level [N-PE] ( $U_P$ )                                     | $\leq 1.5$ kV   |
| Follow current extinguishing capability [N-PE] ( $I_f$ )                      | 100 A <sub>rms</sub>                                    |
| Response time [L-N] ( $t_A$ )   | $\leq 25$ ns  |
| Response time [N-PE] ( $t_A$ )  | $\leq 100$ ns   |
| Max. mains-side overcurrent protection  | 125 A gL/gG   |
| Short-circuit withstand capability for max. mains-side overcurrent protection | 50 kA <sub>rms</sub>                                    |
| Temporary overvoltage (TOV) [L-N] ( $U_T$ )                                   | 175 V / 5 sec.  |
| Temporary overvoltage (TOV) [N-PE] ( $U_T$ )                                  | 1200 V / 200 ms   |
| TOV characteristic  | withstand   |
| Operating temperature range ( $T_U$ )   | -40°C...+80°C   |
| Operating state/fault indication  | green / red   |
| Number of ports   | 1   |
| Cross-sectional area (min.)   | 1.5 mm <sup>2</sup> solid/flexible                      |
| Cross-sectional area (max.)   | 35 mm <sup>2</sup> stranded/25 mm <sup>2</sup> flexible |
| For mounting on   | 35 mm DIN rails acc. to EN 60715                        |
| Enclosure material  | thermoplastic, red, UL 94 V-0                           |
| Place of installation   | indoor installation                                     |
| Degree of protection  | IP 20   |
| Capacity  | 4 module(s), DIN 43880                                  |
| Type of remote signalling contact   | changeover contact                                      |
| a.c. switching capacity   | 250 V/0.5 A   |
| d.c. switching capacity   | 250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A                    |
| Cross-sectional area for remote signalling terminals                          | max. 1.5 mm <sup>2</sup> solid/flexible                 |
| Weight  | 390 g   |
| Customs tariff number   | 85363030  |
| GTIN  | 4013364133242   |
| PU  | 1 pc(s)   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.