

Product Data Sheet: BLITZDUCTOR® XT LifeCheck® Modules




BXT ML2 BE S 48 (920 225)


- LifeCheck SPD monitoring function
- Optimal protection of two single lines and line shield
- For use in conformity with the lightning protection zones concept at the boundaries from $0_A - 2$ and higher



Figure without obligation



Basic circuit diagram BXT ML2 BE S 48



Dimension drawing BXT ML2 BE S 48

Space-saving combined lightning current and surge arrester module with LifeCheck feature for protecting two single lines with common reference potential as well as unbalanced interfaces, with direct or indirect shield earthing. If LifeCheck detects thermal or electrical overload, the arrester has to be replaced. This status is indicated contactlessly by the DEHNrecord LC / MCM reader.

| Type | BXT ML2 BE S 48 |
|--|--|
| Part No. | 920 225 |
| SPD class | TYPE 1P |
| SPD monitoring system | LifeCheck |
| Nominal voltage (U_N) | 48 V |
| Max. continuous operating d.c. voltage (U_C) | 54 V |
| Max. continuous operating a.c. voltage (U_C) | 38.1 V |
| Nominal current at 45°C (I_L) | 0.75 A |
| D1 Total lightning impulse current (10/350 μs) (I_{imp}) | 9 kA |
| D1 Lightning impulse current (10/350 μs) per line (I_{imp}) | 2.5 kA |
| C2 Total nominal discharge current (8/20 μs) (I_n) | 20 kA |
| C2 Nominal discharge current (8/20 μs) per line (I_n) | 10 kA |
| Voltage protection level line-line for I_{imp} D1 (U_p) | ≤ 160 V |
| Voltage protection level line-PG for I_{imp} D1 (U_p) | ≤ 95 V |
| Voltage protection level line-line at 1 kV/ μs C3 (U_p) | ≤ 140 V |
| Voltage protection level line-PG at 1 kV/ μs C3 (U_p) | ≤ 70 V |
| Series resistance per line | 1.8 ohm(s) |
| Cut-off frequency line-PG (f_G) | 8.7 MHz |
| Capacitance line-line (C) | ≤ 0.35 nF |
| Capacitance line-PG (C) | ≤ 0.7 nF |
| Operating temperature range | -40°C...+80°C |
| Degree of protection (with plugged-in protection module) | IP 20 |
| Pluggable into | base part |
| Earthing via | base part |
| Enclosure material | polyamide PA 6.6 |
| Colour | yellow |
| Test standards | IEC 61643-21 / EN 61643-21, UL 497B |
| SIL classification | SIL2 / SIL3 *) |
| ATEX approvals | DEKRA 11ATEX0089 X: II 3 G Ex nA IIC T4 Gc |
| IECEx approvals | DEK 11.0032X: Ex nA IIC T4 Gc |
| CSA & USA Hazloc approvals (1) | 2516389: Class I Div. 2 GP A, B, C, D T4 |
| CSA & USA Hazloc approvals (2) | 2516389: Class I Zone 2, AEx nA IIC T4 |
| Approvals | CSA, UL, GOST, VdS |
| Weight | 21 g |
| Customs tariff number | 85363010 |
| GTIN | 4013364118379 |
| PU | 1 pc(s) |

*) For more detailed information, please visit www.dehn.de/en/sil/

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.